

A-50020N-5-1/8

HAFNER

(HU) Dugaszolható egyenes csatlakozó




Technical data

Kivitel	menetes
Material	Nickel-plated brass
Port size / Connection	G 1/8"
Medium	Compressed air, vacuum
Material seals	NBR
Temperature range	-20°C...+80°C
Operating pressure	-0,9...20 bar
Material retaining ring	Stainless steel
Material support ring	Technopolymer
Pressure range	-0,9...20 bar
Port size Push-in connection	Ø5
Port size	Ø5
Material body	Nickel-plated brass
Material release ring	Technopolymer
Rögzítő karom anyaga	Stainless steel

A-50020N-5-1/8

HAFNER

(HU) Dugaszolható egyenes csatlakozó



Type number	Tube size	Port size A	B	C	L	CH1	CH2
A-50020N-4-M3	4	M 3	3	10	21	8	-
A-50020N-4-M5	4	M 5	4	8	21	10	2
A-50020N-4-1/8	4	G 1/8"	6	13	20	10	3
A-50020N-4-1/4	4	G 1/4"	8	16	19,5	16	3
A-50020N-5-M5	5	M 5	4	8	23,5	12	2
A-50020N-5-1/8	5	G 1/8"	6	13	22	12	4
A-50020N-5-1/4	5	G 1/4"	8	16	22	12	4
A-50020N-6-M5	6	M 5	4	10	24,5	13	2
A-50020N-6-1/8	6	G 1/8"	6	13	23,5	13	4
A-50020N-6-1/4	6	G 1/4"	8	16	23,5	13	4
A-50020N-6-3/8	6	G 3/8"	9	20	25	13	4
A-50020N-6-1/2	6	G 1/2"	10	25	27	13	4
A-50020N-8-1/8	8	G 1/8"	6	13	25	14	5
A-50020N-8-1/4	8	G 1/4"	8	16	23	14	6
A-50020N-8-3/8	8	G 3/8"	9	20	24	14	6
A-50020N-8-1/2	8	G 1/2"	10	25	26,5	14	6
A-50020N-10-1/4	10	G 1/4"	8	16	30,5	17	6
A-50020N-10-3/8	10	G 3/8"	9	20	27,5	17	8
A-50020N-10-1/2	10	G 1/2"	10	25	27	17	8
A-50020N-12-1/4	12	G 1/4"	8	16	34,5	20	6
A-50020N-12-3/8	12	G 3/8"	9	20	34	20	8
A-50020N-12-1/2	12	G 1/2"	10	25	31	22	10
A-50020N-14-3/8	14	G 3/8"	9	20	35	21	10
A-50020N-14-1/2	14	G 1/2"	10	25	32	22	10
A-50020N-6-M12x1	6	M 12 x 1	8	15	23,5	13	4
A-50020N-6-M12x1,25	6	M 12 x 1,25	8	15	23,5	13	4
A-50020N-6-M12x1,5	6	M 12 x 1,5	8	15	23,5	13	4
A-50020N-8-M12x1,5	8	M 12 x 1,5	8	15	27,5	14	6