


QBF 80/40

HAFNER


(HU) UNITOP kompakt henger



Technical data


Port size / Connection	G 1/8"
Piston rod thread	M16 x 1,5 - male thread
Medium	Compressed air
Piston type	Magnetic
Material seals	Polyurethane, NBR
Material heads	Anodized aluminum
Diameter	Ø80
Function	Double acting
Temperature range	-20°C...+80°C
Material body	Anodized aluminum
Material piston	Aluminum
Material guide bushing	Sintered bronze
Piston rod diameter	Ø20 mm
Stroke	40 mm
Operating pressure	1...10 bar
Thrust force	2685 N
Cushioning	Built-in cushioning rings
Material piston rod	Chromed steel (CK45)

QBF 80/40



HAFNER

(HU) UNITOP kompakt henger



Type number	Ø [mm]	A	E	E1	L	M	R	T	AM	EE	KK	LA	PL	RT	SW	WH
QBF 12/...	Ø 12	6	29	1	35	50	18	1,5	16	M 5	M 6	16	6,5	M 4	5	7,5
QBF 16/...	Ø 16	8	29	1	35	52	18	2	20	M 5	M 8	16	6,5	M 4	7	8,5
QBF 20/...	Ø 20	10	36	1,5	39	53	22	2	22	M 5	M 10 x 1,25	18,5	8	M 5	9	7
QBF 25/...	Ø 25	10	40	1,5	39	53	26	2	22	M 5	M 10 x 1,25	18,5	8	M 5	9	7
QBF 32/...	Ø 32	12	50	2	42	56	32	2,8	22	G 1/8"	M 10 x 1,25	21,5	6,5	M 6	10	7
QBF 40/...	Ø 40	12	60	2,5	45,5	62,5	42	2,8	22	G 1/8"	M 10 x 1,25	21,5	7,5	M 6	10	8,5
QBF 50/...	Ø 50	16	68	3	45,5	65,5	50	3,5	24	G 1/8"	M 12 x 1,25	23,5	7,5	M 8	13	10
QBF 63/...	Ø 63	16	87	4	51	72	62	3,5	24	G 1/8"	M 12 x 1,25	28,5	7,5	M 10	13	10,5
QBF 80/...	Ø 80	20	107	4	62	88	82	4,5	32	G 1/8"	M 16 x 1,5	28,5	9,5	M 10	17	13
QBF 100/...	Ø 100	25	128	5	68	99	103	6	40	G 1/4"	M 20 x 1,5	28,5	10,5	M 10	22	15,5